



CMS-4.1

This system proves that compact dimensions and sophisticated style can coexist with high-performance sound. It is an excellent choice for 70V/100V distributed-line systems in applications that require unobtrusive, easy-to-install, high-quality loudspeakers.

Because of its individually sold components that include a low-profile satellite, durable mounting kit, two subwoofer selections and a flexible outboard network, this system can easily be configured to deliver just the right amount of sound to any size installation.


Available in black or white, the satellite is a marvel of miniature technology that maximizes output and dynamics. Klipsch's exclusive MicroTractrix™ Horn, the working element of this 7.5-inch tall loudspeaker, is formed right into the cabinet baffle, a design that offers the lowest diffraction and maximum release of energy into the listening areas. The ported, bass-reflex enclosure maximizes bass response for a dynamic sound.

Also available in black or white, the Comm Sat mounting kit features a metal wall plate and arm that offers both tilt and swivel features. Once properly positioned, the pivoting tip can easily be locked into place with the provided adjustment tool. To enhance the cosmetics of the finished installation, the satellite's color-matched wire can be concealed in the mount arm.

As one of the subwoofer options, the compact, easy-to-install surface mount CA-SW-8T is an all-purpose, indoor/outdoor passive model with an internal multi-tap transformer. This product delivers deep, driving sound through an 8-inch, long excursion driver that has a high-temperature voice coil attached to an IMG (injection-molded graphite) cone that combines light weight, excellent rigidity, and water resistance. For easy wall or ceiling mounting, the CA-SW-8T comes with a C-bracket assembly that attaches to threaded studs in the cabinet with oversized knobs, ensuring positive lock.

SPECIFICATIONS

COMM SAT NETWORK



BANDWIDTH ¹	N/A
TRANSFORMER TAPS	70V: 30 Watt, 100V: 60 Watt
CROSSOVER	100Hz 12dB/Octave Highpass
INPUT CONNECTORS	Barrier Strip
ENCLOSURE MATERIAL	Steel
HEIGHT	4.375" (11.1 cm)
WIDTH	6.125" (15.6 cm)
DEPTH	6.125" (15.6 cm)
WEIGHT	5 lbs. (2.3 kg)
FINISH	Gray

COMM SAT SPEAKER



BANDWIDTH ¹	120Hz-20kHz ± 4dB (-10dB @ 42Hz)
POWER HANDLING ²	70W (15.5V @ 3.2 ohm input)
MAXIMUM CONTINUOUS SPL ³	107 dB
SENSITIVITY ⁴	92dB @ 2.83 volts/1 meter
TRANSFORMER TAPS	N/A (Comm Sat network required)
NOMINAL IMPEDANCE	8 ohms (3.2 ohm minimum @ 5.5Hz)
HIGH FREQUENCY CROSSOVER	4900Hz
DRIVE COMPONENTS	Two-way system using one .75" (1.9cm) magnetically shielded, polymer dome compression driver tweeter with a 90° x 40° Tractrix® Horn and one 3.5" (8.9cm) magnetically shielded, poly cone woofer
SYSTEM CROSSOVER	Comm Sat network required
INPUT CONNECTORS	Pig tail wire attached
ENCLOSURE TYPE	Bass reflex via rear-mounted port
ENCLOSURE MATERIAL	Stone Mineral Compound
HEIGHT	7.5" (19.1 cm)
WIDTH	4.25" (10.8 cm)
DEPTH	6.4" (16.2 cm)
NET WEIGHT	4 lbs. (1.8 kg)/ each
SHIPPING WEIGHT	8 lbs. (3.6 kg)/ pair
FINISH	Black or White
MOUNTING	Comm Sat mount (optional)

¹ 3M, Half-space anechoic

² AES Standard, continuous pink noise 50Hz-10kHz, 6dB peaks

³ Calculated at 1M half-space at power handling power input

⁴ SPL at 1M, half-space anechoic with 2.83V input



CMS-4.1

Continued from page 1

Also compact and easy-to-install, the IC-8T-SW in-ceiling subwoofer option features a transformer-less design that delivers high-impact, robust bass. This model adds more dimension to any in-ceiling configuration by using an 8-inch woofer and 8-inch drone, both featuring polypropylene cones and high-temperature voice coils in the woofer. While most subwoofers use a port to increase output, the IC-8T-SW employs a bandpass design that utilizes a passive radiator. This eliminates a lot of the distortion and minimizes turbulence that is often present in ported designs. The IC-8T-SW is shipped complete with a tilebridge for installation in a suspended ceiling or wherever additional reinforcement of the ceiling material is required.

Specifically designed for this system, the Comm Sat Network is an outboard unit that features 70V/100V tap-settings and serves as a hub for up to four satellites and the chosen subwoofer. It is housed in an integral UL-approved metal box.

SUBWOOFER OPTIONS

CA-SW-8T



BANDWIDTH ¹	51-135Hz ± 4dB (-10dB 42Hz)
POWER HANDLING ²	150W (25V @ 6 ohm input)
MAX CONTINUOUS OUTPUT ³	111dB
SENSITIVITY ⁴	92dB @ 2.83 volts/1 meter
TRANSFORMER TAPS	70V: 60W, 30W, 15W, 7.5W 100V: 60W, 30W, 15W Thru Position: 6 ohms
NOMINAL IMPEDANCE	6 ohms nominal (4 Minimum @ 92Hz)
LOW FREQUENCY CROSSOVER	12dB/Octave low-pass, 150Hz
DRIVE COMPONENTS	One 8" IMG cone woofer
INPUT CONNECTORS	5-way binding posts
ENCLOSURE TYPE	Bass reflex via front mounted port
ENCLOSURE MATERIAL	All-weather ABS Plastic
HEIGHT	11.125" (28.3cm)
WIDTH	16.375" (41.5cm)
DEPTH	11.75" (29.9cm)
NET WEIGHT	19 lbs. (8.6kg)
SHIPPING WEIGHT	22.1 lbs. (10kg)
FINISH	Black or White
MOUNTING	C-Bracket (included); CA Safety Kit (optional)

IC-8T-SW



BANDWIDTH ¹	53-129Hz ± 4dB (-10dB 44Hz)
POWER HANDLING ²	150W (27V @ 6 ohm input)
MAX CONTINUOUS OUTPUTS ³	111dB
SENSITIVITY ⁴	92dB @ 2.83 volts/1 meter
SWITCH TAPS	4 ohm Mono position Thru Position: 4 ohm Mono or 8 ohm Stereo
TRANSFORMER	70/100V Position- 60W/120W
NOMINAL IMPEDANCE	6 ohms (4.85 minimum @145Hz)
LOW FREQUENCY CROSSOVER	N/A
DRIVE COMPONENTS	One 8" woofer and one 8" drone, Polypropylene cone
INPUT CONNECTORS	4 point terminal strip
ENCLOSURE TYPE	Bandpass enclosure (drone loaded)
ENCLOSURE MATERIAL	Baffle: ABS Plastic, Can: Formed Steel
HEIGHT	13.625" (34.6cm)
DIAMETER	14.125" (35.9cm); 12.5" (cutout diameter)
NET WEIGHT	23 lbs. (10.4 kg)
SHIPPING WEIGHT	30 lbs. (13.6kg)
MOUNTING DEPTH	11.25" (29.9cm)
FINISH	White
MOUNTING	Tilebridge (included)

¹ 3M, Half-space anechoic
² AES Standard, continuous pink noise 50Hz-10kHz, 6dB peaks
³ Calculated at 1M half-space at power handling power input
⁴ SPL at 1M, half-space anechoic with 2.83V input